

Cradle with PINS

Installation instructions

The Sporttraxx FIA/22 tracker must be installed on the dashboard top, horizontally, in a central position that can be reached by both crew members with fastened seat belts.

The upper side of the tracker should have proper view to the sky through the windscreen. Buttons and LEDs face must point toward the crew in order to notice RED FLAG warnings and manage any other signalling from/to race control.



Before technical scrutineering

The safety strap must be inserted into its dedicated slits before the cradle is fitted to the dashboard.

The Sporttraxx FIA/22 cradle must be fixed

1. Inserting and fastening the 4 nylon pins with their nuts
2. Using the double sided special adhesive for its first positioning on the dashboard
3. Screwing the 4 provided screws to safely lock the cradle on the dashboard

Eventually use different screws (longer/shorter or self-drilling) depending on the material of the dashboard. The perspex cradle must be strongly fitted to the dashboard



During technical scrutineering

The Sporttraxx FIA/22 tracker is fitted on its perspex base, by the Sporttraxx technicians, inserting it on the nylon pins. The velcro safety strap must then be closed around the tracker.

How to remove the tracker

Open the velcro safety strip, pull out the tracker from the nylon pins.

Return of the tracker

Trackers are collected upon arrival at final parc fermè by Sporttraxx technicians. In case of early retirement, please make sure to return the tracker asap **only to authorized people**. You are eventually responsible for its loss.

Keep the Sporttraxx FIA/22 cradle in its place for the next event. It fits with 4 different Sporttraxx trackers.