FIA WORLD RALLY-RAID CHAMPIONSHIP

TRUCK VEHICLE SCRUTINEERING SHEET

EVENT: MAROC 2026	**TRUCK NUMBER:**
Official scrutineering time:	**Actual presentation time:**
FIA TECH. PASS.:	**CLASS:** T5.1 | T5.2
TRUCK MAKE & MODEL:	**VIN NUMBER:**

Compulsory for T5.1 vehicles only — **Applicable for T5.2 vehicles only**

Ref			OK	NOT OK	REMARKS	Solved
	BODYWORK					
283-10	**HORN/LIGHTS**	*Headlights, indicators, rear & stop lights*				
283-16	**ADDITIONAL RED REAR LIGHTS**	*2 FOG lights + 2 add. STOP lights*				
SR-8.1	**REGISTRATION PLATES**	*Front & rear*				
283-13	**EXTERNAL CIRCUIT BREAKER**	*Test*			*To be performed by the team!*	
		Sticker - External - 12cm mini				
283-10	**TOWING EYES**	*front & rear + red/yellow/ orange*				
287-5.5	**EXHAUST LINE**	*Behind the cabin & at least 2200mm high + not oriented downwards*				
287- App. I-2.3	If production exhaust system, unmodified except outlet that must not point downwards					
SR-21.1	**DRIVER/ CO-DRIVER NAMES ~~& Flags~~**	*On front wings or doors, from 30 to 50mm high*			*No flags allowed!!*	
Ref	**MANDATORY SAFETY EQUIPEMENT**		**OK**	**NOT OK**	**REMARKS**	**Solved**
SR-48.2.5	**OK/ SOS SIGN**	*A3 format in the cockpit*				
283-6.1.3	**SEAT BELT CUTTERS**	*one per crew member + easily accessible*				
SR-App. III	**MEDICAL KIT**	*Validity*			*Specify Supplier*	
		In the cockpit + properly fastened				
SR-App. IV	**SURVIVAL KIT**	*Triangle, MX googles x "3", safety vests x "3", safety light, towing belt x 9m hand shovel + headlamp 1000lum, 5L water reserve*				
Ref	**CABIN**		**OK**	**NOT OK**	**REMARKS**	**Solved**
283-8.1 & RH for SC	**SAFETY CAGE**	*Compliance with certificate*				
		Design in compliance with (current) RH for SC requirements				
		Damaged/ Modified				
		Improperly welded				
287- App. I-1.1	**SAFETY CAGE FOR T1.2**	*Compliance with the requirements of the art. 1.1 of the Appendix I*				
283-4	**STEERING COLUMN**	*Adjustment only possible by tools*				
		Quick release system -> Yellow			*Optional*	
	Steering wheel padding	*Surface ≥ 200cm² & foam quality -> CF45M => Blue*				
283-20.2	**ANCHORAGES FOR SEAT SUPPORTS**	*Surface ≥ 40cm²*				
		Properly welded				
283-20.1	**SEATS (TL N°12)**	***Driver:*** *Global status + validity*			*Specify Homologation Nb*	
		Engineer: *Global status + validity*			*Specify Homologation Nb*	
		Codriver: *Global status + validity*			*Specify Homologation Nb*	
283-20.3	**SEAT SUPPORTS**	*Steel 3mm or Alu 5mm, single piece*				
		Intermediate seat bracket/ supports?			*Material? Thickness? Design? =>* ***Photos needed***	
		Surface under bolts heads/washers				
283-6	**SAFETY HARNESSES (TH N°57)**	***Driver:*** *Global status + validity*				
		Engineer: *Global status + validity*				
		Codriver: *Global status + validity*				
		Seat belts anchorages				
		Seat belts buckles (with pin) + no additional part				
283-7.2	**MANUAL EXTINGUISHER I**	*In the cabin and easily accessible*				
		Validity				
	Fixing	*2 quick-rel. metal straps & anti-torpedo tabs*				
	MANUAL EXTINGUISHER II	*In the cabin and easily accessible*				
		Validity				
	Fixing	*2 quick-rel. metal straps & anti-torpedo tabs*				

Ref	CABIN		OK	NOT OK	REMARKS	Solved
283-7.1	EXTINGUISHER(S) SYSTEMS (TL N°52) /!\ Type of ext. agent must be OK for Diesel + installation must be adapted to cabin volume	Extinguisher syst I Validity			OMP EX.022.19 or EX.023.19	
		Extinguisher syst II Validity			OMP EX.022.19 or EX.023.19 If none, specify NONE	
	Box position	Accessible for at least one crew member				
	2 X Bottle fixing	2 screw-locked metallic straps & anti-torpedo tabs				
	Nozzles (cockpit and engine bay)	Positions according instal. Guidelines				
		Mechanically secured				
	Lines	No extinguisher pipes between safety cage and cabin				
	Position	botton Position (on front)				
	Test	test			To be performed by the team!	
	External trigger & "E" sign	Sticker - 10cm mini				
283-8.3	ELECTRICAL LINES	No electric wire between safety cage & cabin				
283-3.3.3	BRAKE/ CLUTCH TANKS	Protection if in cabin (fireproof...)				
283-11	LATERAL WINDOWS	Film on glass windows				
283-11	WINDOW NETS	May be affixed on door				
		Upper part not removable without tools				
287.3.3.2.3	CAB AND BONNET LOCK DOWN	Must have additional devices				
Ref	**CARGO BODY**		**OK**	**NOT OK**	**REMARKS**	**Solved**
283-8.2	SAFETY CAGE	Main rollbar design				
	Main rollbar	Compliance with minimum dimensions				
		Mountings: fixation + surface areas				
		Mounting on the main rollbar				
	Backstays	Compliance with minimum dimensions				
		Mountings: fixation + surface areas				
283-5	TOOLS/ SPARE PARTS	Fastened securely				
283-7.2	MANUAL EXTINGUISHERS 6kg	Validities				
	Fixing	2 quick-rel. metal straps & anti-torpedo tabs				
		Sticker x 2 - 10cm mini				
		Easily accessible from outside				
Ref	**FUEL TANK**		**OK**	**NOT OK**	**REMARKS**	**Solved**
287-1.3	FUEL TANK TYPE		FT3	Metal	Circle the relevant box	
	FT3 FUEL BLADDER	Manufacturer, certification & validity				
	FT3 FUEL BLADDER HOUSING	Aluminium - 3mm mini				
	METAL FUEL TANKS	Number (Maximum 5)		X	Specify total number of tanks, bigger than 6L	
		Capacity of the biggest tank			Max 500L	
		Modifications: only the ones allowed				
	FUEL TANK(S) POSITIONS	In the wheelbase				
		Under a line joining rearmost point of chassis & top of cargo body rollbar				
	FUEL TANK(S) UNDERBODY PROTECTION	5mm Al or 10mm composite mini			Only if located below and/or outside chassis rails!	
	FUEL TANK(S) FIXATION	Strap: steel + section > 120mm² each				
		At least 2 straps per tank				
287- App. I-1.3		Capacity of the biggest tank			Max 800L	
	Behind the rearmost axle **but** in between the chassis frame rails **&** in front of the rearmost point of the beams					
283-14.2	VENTING	Roll-over valve + blow-off valve, per tank			Specify reference	
		Vent lines installation (no U)				
Ref	**ELECTRICAL EQUIPMENT**		**OK**	**NOT OK**	**REMARKS**	**Solved**
287-11.3.4	BATTERY(IES)	Positive terminal protected				
		Location				
		Fixation				
Ref	**SEALING**		**OK**	**NOT OK**	**REMARKS**	**Solved**
SR-24.1.1	ENGINE BLOCK				Seal/ sticker Nb	
SR-24.1.2	RESTRICTOR	Not required if comp. housing inlet ⌀ < 74mm; if so, housing must be sealed			Seal/ sticker Nb Seal Nb A Seal Nb B	

Additional Notes:

DATE: / / HOUR:

VEHICLE APPROVED YES NO

TEAM REPRESENTATIVE

(Name & Signature)

SCRUTINEER

(Name & Signature)

RE-SCRUTINY

DATE: / / HOUR:

VEHICLE APPROVED YES NO

SCRUTINEER

(Name & Signature)